

■ 定格総荷重表

■ メインブーム

作業半径 (m)	A性能					
	12m ブーム	16.4m ブーム	20.75m ブーム	29.5m ブーム	38.3m ブーム	47m ブーム
2.5m	120.0					
2.7m	110.0					
3.0m	100.0	50.0	38.0			
3.5m	86.0	50.0	38.0			
4.0m	77.0	50.0	38.0	32.0		
5.0m	64.0	50.0	38.0	32.0		
6.0m	54.0	50.0	38.0	32.0	24.0	
7.0m	46.0	44.0	38.0	31.0	24.0	12.0
8.0m	39.5	37.5	36.2	28.5	23.4	12.0
9.0m	33.0	32.7	32.5	26.0	21.3	12.0
10.0m		29.2	29.0	23.5	19.5	12.0
11.0m		25.7	25.5	21.4	17.9	12.0
12.0m		22.8	22.6	19.6	16.5	12.0
14.0m			17.0	16.6	14.2	11.7
16.0m			13.2	14.3	12.4	10.2
18.0m				11.8	10.9	9.0
20.0m				9.6	9.6	8.0
22.0m				7.9	8.4	7.1
24.0m				6.5	7.2	6.4
26.0m				5.2	6.0	5.8
28.0m					5.0	5.2
30.0m					4.0	4.4
32.0m					3.1	3.6
34.0m					2.4	2.8
36.0m						2.2
38.0m						1.6
40.0m						1.1
フック重量	1,400kg	880kg	625kg	625kg	625kg	625kg
ロープ掛数	18本	8本	6本	6本	4本	4本
ブーム最小角度	—	—	—	—	18°	24.5°

(単位: ton)

■ スーパーラフィングジブ

● 47mブーム+8.4m SLジブ

作業半径 (m)	A性能							
	オフセット2°		オフセット15°		オフセット30°		オフセット45°	
	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重
9.0m	81.1°	5.60						
10.0m	80.2°	5.60						
11.0m	79.2°	5.60	81.0°	5.50				
12.0m	78.3°	5.60	80.0°	5.50				
14.0m	76.3°	5.60	78.0°	5.50	79.7°	5.25	81.0°	4.10
16.0m	74.3°	5.60	76.0°	5.50	77.7°	5.00	79.0°	3.95
18.0m	72.3°	5.60	74.0°	5.20	75.6°	4.75	76.9°	3.85
20.0m	70.1°	5.10	72.0°	4.95	73.7°	4.50	74.7°	3.75
22.0m	67.9°	4.55	69.8°	4.40	71.5°	4.10	72.6°	3.65
24.0m	65.8°	4.00	67.6°	3.90	69.2°	3.70	70.3°	3.45
26.0m	63.5°	3.50	65.3°	3.45	66.9°	3.30	68.0°	3.25
28.0m	61.2°	2.95	63.1°	3.05	64.5°	2.95	65.3°	2.95
30.0m	58.8°	2.50	60.7°	2.70	62.1°	2.65	63.0°	2.65
32.0m	56.4°	2.15	58.2°	2.25	59.5°	2.35	60.4°	2.35
34.0m	53.8°	1.65	55.6°	1.90	57.0°	2.00	57.7°	2.00
36.0m			52.9°	1.25	54.2°	1.55	54.6°	1.65
38.0m					51.4°	0.85	51.6°	0.95
フック重量	250kg		250kg		250kg		250kg	
ロープ掛数	1本		1本		1本		1本	
ブーム最小角度	49.5°		49.5°		48°		48.5°	

(単位: ton)

● 47mブーム+14.7m SLジブ

作業半径 (m)	A性能							
	オフセット2°		オフセット15°		オフセット30°		オフセット45°	
	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重
11.0m	81.0°	3.80						
12.0m	80.2°	3.80						
14.0m	78.4°	3.80	80.4°	3.80				
16.0m	76.7°	3.80	78.8°	3.65				
18.0m	74.9°	3.80	77.2°	3.40	79.6°	2.40		
20.0m	73.0°	3.80	75.5°	3.20	77.8°	2.30	80.0°	1.80
22.0m	71.1°	3.55	73.5°	3.00	75.9°	2.20	78.1°	1.75
24.0m	69.1°	3.35	71.6°	2.80	73.9°	2.10	75.9°	1.70
26.0m	67.1°	3.10	69.6°	2.65	71.9°	2.00	73.8°	1.65
28.0m	65.1°	2.85	67.6°	2.50	69.8°	1.95	71.6°	1.60
30.0m	63.2°	2.55	65.6°	2.35	67.8°	1.90	69.4°	1.55
32.0m	61.1°	2.20	63.7°	2.20	65.8°	1.80	67.2°	1.55
34.0m	58.7°	1.90	61.7°	1.95	63.7°	1.75	65.1°	1.50
36.0m	56.5°	1.60	59.4°	1.70	61.4°	1.70	62.9°	1.50
38.0m	54.2°	1.30	56.9°	1.45	59.1°	1.50	60.5°	1.45
40.0m			54.5°	1.20	56.8°	1.30	58.0°	1.30
42.0m					53.9°	1.05	55.1°	1.15
フック重量	250kg		250kg		250kg		250kg	
ロープ掛数	1本		1本		1本		1本	
ブーム最小角度	51°		51°		51°		52°	

(単位: ton)

● 47mブーム+21m SLジブ

作業半径 (m)	A性能							
	オフセット2°		オフセット15°		オフセット30°		オフセット45°	
	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重
14.0m	80.0°	2.20						
16.0m	78.4°	2.20						
18.0m	76.8°	2.20	79.7°	2.00				
20.0m	75.1°	2.20	78.1°	1.85				
22.0m	73.5°	2.20	76.6°	1.75	80.0°	1.25		
24.0m	71.8°	2.20	74.9°	1.65	78.4°	1.20		
26.0m	70.1°	2.20	73.1°	1.55	76.7°	1.15	79.5°	0.90
28.0m	68.3°	2.05	71.4°	1.45	75.0°	1.10	77.7°	0.85
30.0m	66.5°	1.90	69.7°	1.40	73.2°	1.05	75.8°	0.85
32.0m	64.7°	1.75	68.0°	1.30	71.2°	1.00	73.9°	0.80
34.0m	62.8°	1.65	66.3°	1.25	69.2°	0.95	71.9°	0.80
36.0m	61.0°	1.55	64.4°	1.20	67.2°	0.90	69.8°	0.75
38.0m	58.9°	1.35	62.4°	1.15	65.3°	0.90	67.6°	0.75
40.0m	56.8°	1.15	60.3°	1.10	63.4°	0.85	65.4°	0.70
42.0m	54.8°	0.95	58.3°	1.00	61.2°	0.80	63.1°	0.70
44.0m			56.1°	0.90	58.9°	0.80	60.6°	0.70
46.0m					56.7°	0.75	58.1°	0.70
48.0m							55.5°	0.70
フック重量	250kg		250kg		250kg		250kg	
ロープ掛数	1本		1本		1本		1本	
ブーム最小角度	51°		52°		53°		55.5°	

(単位: ton)