

■LA性能 4.4m+53mラフィングジブ

単位: t

| ブーム長さ 作業半径 (m) | 30.9m オフセット | | | | 35.2m オフセット | | | | 39.4m オフセット | | | | | 43.7m オフセット | | | | |
|----------------------|----------------|-----------|-----------|-----------|----------------|-----------|-----------|-----------|----------------|-----------|-----------|-----------|-----------|----------------|-----------|-----------|-----------|-----------|
| | 10° | 20° | 30° | 45° | 10° | 20° | 30° | 45° | 10° | 20° | 30° | 45° | 60° | 10° | 20° | 30° | 45° | 60° |
| 26.0 | 9.7 | | | | 8.2 | | | | | | | | | | | | | |
| 28.0 | 9.7 | | | | 8.2 | | | | 7.0 | | | | | | | 5.7 | | |
| 30.0 | 9.7 | | | | 8.2 | | | | 7.0 | | | | | | | 5.7 | | |
| 32.0 | 9.7 | | | | 8.2 | | | | 7.0 | | | | | | | 5.7 | | |
| 34.0 | 9.7 | 9.7 | | | 8.2 | 8.2 | | | 7.0 | | | | | | | 5.7 | | |
| 36.0 | 9.7 | 9.7 | | | 8.2 | 8.2 | | | 7.0 | 7.0 | | | | | | 5.7 | 5.7 | |
| 38.0 | 9.7 | 9.5 | | | 8.2 | 8.2 | | | 7.0 | 7.0 | | | | | | 5.7 | 5.7 | |
| 40.0 | 9.7 | 9.3 | | | 8.2 | 8.2 | | | 7.0 | 7.0 | | | | | | 5.7 | 5.7 | |
| 42.0 | 9.6 | 9.1 | 8.7 | | 8.2 | 8.2 | 8.2 | | 7.0 | 7.0 | 7.0 | | | | | 5.7 | 5.7 | |
| 44.0 | 9.4 | 8.9 | 8.5 | | 8.2 | 8.2 | 8.2 | | 7.0 | 7.0 | 7.0 | | | | | 5.7 | 5.7 | 5.7 |
| 46.0 | 9.2 | 8.8 | 8.4 | | 8.2 | 8.2 | 8.2 | | 7.0 | 7.0 | 7.0 | | | | | 5.7 | 5.7 | 5.7 |
| 48.0 | 9.0 | 8.6 | 8.3 | | 8.2 | 8.2 | 8.2 | | 7.0 | 7.0 | 7.0 | | | | | 5.7 | 5.7 | 5.7 |
| 50.0 | 8.8 | 8.5 | 8.1 | 7.8 | 8.2 | 8.2 | 8.2 | | 7.0 | 7.0 | 7.0 | | | | | 5.7 | 5.7 | 5.7 |
| 55.0 | 8.4 | 8.1 | 7.9 | 7.6 | 8.2 | 8.2 | 7.9 | 7.6 | 7.0 | 7.0 | 7.0 | 7.0 | | | | 5.7 | 5.7 | 5.7 |
| 60.0 | 7.9 | 7.8 | 7.6 | 7.5 | 7.6 | 7.9 | 7.7 | 7.5 | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | | 5.7 | 5.7 | 5.7 |
| 65.0 | 6.4 | 7.1 | 7.5 | 7.4 | 6.1 | 6.9 | 7.5 | 7.4 | 5.8 | 6.6 | 7.0 | 7.0 | 7.0 | | | 5.6 | 5.7 | 5.7 |
| 70.0 | 5.1 | 5.6 | | 6.2 | 4.7 | 5.4 | 6.0 | | 4.4 | 5.2 | 5.8 | 6.7 | | | | 4.3 | 5.0 | 5.7 |
| 75.0 | 3.9 | 4.4 | | | 3.6 | 4.1 | 4.6 | | 3.3 | 3.9 | 4.4 | | | | | 3.1 | 3.8 | 4.4 |
| 80.0 | 2.3 | | | | 2.5 | 3.0 | | | 2.3 | 2.8 | 3.2 | | | | | 2.1 | 2.7 | 3.1 |
| 85.0 | | | | | | | | | | 1.7 | | | | | | | 1.7 | |
| θ (°) | 28 ~ 81.5 | 41 ~ 81.5 | 52 ~ 81.5 | 63 ~ 81.5 | 34 ~ 81.5 | 38 ~ 81.5 | 49 ~ 81.5 | 65 ~ 81.5 | 38 ~ 81.5 | 36 ~ 81.5 | 46 ~ 81.5 | 62 ~ 81.5 | 76 ~ 81.5 | 42 ~ 81.5 | 40 ~ 81.5 | 50 ~ 81.5 | 64 ~ 81.5 | 77 ~ 81.5 |
| 標準フック フック質量 | 12.5t 490kg | | | | | | | | | | | | | | | | | |
| 標準巻掛本数 | 1 | | | | | | | | | | | | | | | | | |

| ブーム長さ 作業半径 (m) | 47.9m オフセット | | | | | 52.2m オフセット | | | | | 56.4m オフセット | | | |
|----------------------|----------------|-----------|-----------|-----------|-----------|----------------|-----------|-----------|-----------|-----------|----------------|-----------|-----------|-----------|
| | 10° | 20° | 30° | 45° | 60° | 10° | 20° | 30° | 45° | 60° | 10° | 20° | 30° | 45° |
| 28.0 | 4.2 | | | | | | | | | | | | | |
| 30.0 | 4.2 | | | | | 3.0 | | | | | | | | |
| 32.0 | 4.2 | | | | | 3.0 | | | | | | | | |
| 34.0 | 4.2 | | | | | 3.0 | | | | | | | | |
| 36.0 | 4.2 | | | | | 3.0 | | | | | | | | |
| 38.0 | 4.2 | 4.2 | | | | 3.0 | 3.0 | | | | | | | |
| 40.0 | 4.2 | 4.2 | | | | 3.0 | 3.0 | | | | | 2.2 | | |
| 42.0 | 4.2 | 4.2 | | | | 3.0 | 3.0 | | | | | 2.2 | 2.2 | |
| 44.0 | 4.2 | 4.2 | 4.2 | | | 3.0 | 3.0 | | | | | 2.2 | 2.2 | |
| 46.0 | 4.2 | 4.2 | 4.2 | | | 3.0 | 3.0 | 3.0 | | | | 2.2 | 2.2 | 2.2 |
| 48.0 | 4.2 | 4.2 | 4.2 | | | 3.0 | 3.0 | 3.0 | | | | 2.2 | 2.2 | 2.2 |
| 50.0 | 4.2 | 4.2 | 4.2 | | | 3.0 | 3.0 | 3.0 | | | | 2.2 | 2.2 | 2.2 |
| 55.0 | 4.2 | 4.2 | 4.2 | 4.2 | | 3.0 | 3.0 | 3.0 | 3.0 | | | 2.2 | 2.2 | 2.2 |
| 60.0 | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | | 2.2 | 2.2 | 2.2 |
| 65.0 | 4.2 | 4.2 | 4.2 | 4.2 | | 3.0 | 3.0 | 3.0 | 3.0 | | | 2.2 | 2.2 | 2.2 |
| 70.0 | 4.1 | 4.2 | 4.2 | 4.2 | | 3.0 | 3.0 | 3.0 | 3.0 | | | 2.2 | 2.2 | 2.2 |
| 75.0 | 3.0 | 3.7 | 4.0 | 4.2 | | 2.6 | 2.9 | 3.0 | 3.0 | | | 1.8 | 2.0 | 2.2 |
| 80.0 | 2.0 | 2.6 | 3.1 | | | 1.9 | 2.2 | 2.5 | | | | | 1.5 | 1.7 |
| 85.0 | | 1.6 | 2.0 | | | | | 1.5 | 1.8 | | | | | |
| θ (°) | 44 ~ 81.5 | 44 ~ 81.5 | 47 ~ 81.5 | 61 ~ 81.5 | 78 ~ 81.5 | 47 ~ 81.5 | 47 ~ 81.5 | 50 ~ 81.5 | 63 ~ 81.5 | 79 ~ 81.5 | 53 ~ 81.5 | 53 ~ 81.5 | 56 ~ 81.5 | 65 ~ 81.5 |
| 標準フック フック質量 | 12.5t 490kg | | | | | | | | | | | | | |
| 標準巻掛本数 | 1 | | | | | | | | | | | | | |

注) カウンタウエイト105t、アウトリガ張出幅 8.7m

■LA性能 4.4m+58mラフィングジブ

単位: t

| ブーム長さ 作業半径 (m) | 13.9m オフセット | | | | | 18.2m オフセット | | | | | 22.4m オフセット | | | | | 26.7m オフセット | | | | |
|----------------------|----------------|-----------|-----------|-----------|-----------|----------------|-----------|-----------|-----------|-----------|----------------|-----------|-----------|-----------|-----------|----------------|-----------|-----------|-----------|-----------|
| | 10° | 20° | 30° | 45° | 60° | 10° | 20° | 30° | 45° | 60° | 10° | 20° | 30° | 45° | 60° | 10° | 20° | 30° | 45° | 60° |
| 24.0 | 8.0 | | | | | 8.0 | | | | | 7.6 | | | | | | | | | |
| 26.0 | 8.0 | | | | | 8.0 | | | | | 7.6 | | | | | | | | | |
| 28.0 | 8.0 | | | | | 8.0 | | | | | 7.6 | | | | | | | | | |
| 30.0 | 8.0 | | | | | 8.0 | | | | | 7.6 | | | | | | | | | |
| 32.0 | 8.0 | 8.0 | | | | 8.0 | | | | | 7.6 | | | | | | | | | |
| 34.0 | 8.0 | 8.0 | | | | 8.0 | 8.0 | | | | 7.6 | 7.6 | | | | | | | | |
| 36.0 | 8.0 | 7.9 | | | | 8.0 | 8.0 | | | | 7.6 | 7.6 | | | | | | | | |
| 38.0 | 7.9 | 7.7 | | | | 8.0 | 7.7 | | | | 7.6 | 7.6 | | | | | | | | |
| 40.0 | 7.7 | 7.4 | 7.1 | | | 7.8 | 7.5 | | | | 7.6 | 7.6 | | | | | | | | |
| 42.0 | 7.4 | 7.2 | 6.9 | | | 7.5 | 7.3 | 7.0 | | | 7.6 | 7.4 | 7.1 | | | | | | | |
| 44.0 | 7.2 | 7.0 | 6.7 | | | 7.3 | 7.1 | 6.8 | | | 7.5 | 7.2 | 6.9 | | | | | | | |
| 46.0 | 7.1 | 6.8 | 6.6 | | | 7.2 | 6.9 | 6.7 | | | 7.3 | 7.1 | 6.7 | | | | | | | |
| 48.0 | 6.9 | 6.6 | 6.4 | | | 7.0 | 6.8 | 6.5 | | | 7.1 | 6.9 | 6.6 | | | | | | | |
| 50.0 | 6.7 | 6.5 | 6.3 | 6.0 | | 6.8 | 6.6 | 6.3 | | | 6.9 | 6.7 | 6.4 | | | | | | | |
| 55.0 | 6.3 | 6.1 | 5.9 | 5.7 | | 6.4 | 6.2 | 6.0 | 5.8 | | 6.5 | 6.4 | 6.1 | 5.8 | | | | | | |
| 60.0 | 5.9 | 5.8 | 5.7 | 5.5 | 5.4 | 6.1 | 5.9 | 5.7 | 5.6 | 5.4 | 6.2 | 6.0 | 5.8 | 5.6 | 5.4 | 5.4 | | | | |
| 65.0 | 5.6 | 5.5 | 5.5 | 5.4 | | 5.8 | 5.6 | 5.5 | 5.4 | | 5.9 | 5.8 | 5.6 | 5.4 | 5.4 | | | | | |
| 70.0 | 5.4 | 5.4 | 5.4 | | | 5.5 | 5.4 | 5.4 | | | 5.7 | 5.5 | 5.4 | 5.4 | | | | | | |
| 75.0 | | | | | | 5.3 | 5.3 | | | | 5.4 | 5.4 | 5.3 | | | | | | | |
| 80.0 | | | | | | | | | | | 3.8 | | | | | | | | | |
| 85.0 | | | | | | | | | | | | | | | | | | | | |
| θ (°) | 28 ~ 81.5 | 35 ~ 81.5 | 40 ~ 81.5 | 58 ~ 81.5 | 74 ~ 81.5 | 25 ~ 81.5 | 31 ~ 81.5 | 46 ~ 81.5 | 62 ~ 81.5 | 76 ~ 81.5 | 23 ~ 81.5 | 38 ~ 81.5 | 43 ~ 81.5 | 57 ~ 81.5 | 70 ~ 81.5 | 20 ~ 81.5 | 35 ~ 81.5 | 48 ~ 81.5 | 61 ~ 81.5 | 72 ~ 81.5 |
| 標準フック フック質量 | 12.5t 490kg | | | | | | | | | | | | | | | | | | | |
| 標準巻掛本数 | 1 | | | | | | | | | | | | | | | | | | | |

| ブーム長さ 作業半径 (m) | 30.9m オフセット | | | | | 35.2m オフセット | | | | | 39.4m オフセット | | | | | 43.7m オフセット | | | | |
|----------------------|----------------|-----------|-----------|-----------|-----------|----------------|-----------|-----------|-----------|-----------|----------------|-----------|-----------|-----------|-----------|----------------|-----------|-----------|-----------|-----------|
| | 10° | 20° | 30° | 45° | 60° | 10° | 20° | 30° | 45° | 60° | 10° | 20° | 30° | 45° | 60° | 10° | 20° | 30° | 45° | 60° |
| 26.0 | 6.4 | | | | | | | | | | | | | | | | | | | |
| 28.0 | 6.4 | | | | | 5.5 | | | | | 4.7 | | | | | | | | | |
| 30.0 | 6.4 | | | | | 5.5 | | | | | 4.7 | | | | | | | | | |
| 32.0 | 6.4 | | | | | 5.5 | | | | | 4.7 | | | | | | | | | |
| 34.0 | 6.4 | | | | | 5.5 | | | | | 4.7 | | | | | | | | | |
| 36.0 | 6.4 | 6.4 | | | | 5.5 | 5.5 | | | | 4.7 | | | | | | | | | |
| 38.0 | 6.4 | 6.4 | | | | 5.5 | 5.5 | | | | 4.7 | 4.7 | | | | | | | | |
| 40.0 | 6.4 | 6.4 | | | | 5.5 | 5.5 | | | | 4.7 | 4.7 | | | | | | | | |
| 42.0 | 6.4 | 6.4 | | | | 5.5 | 5.5 | | | | 4.7 | 4.7 | | | | | | | | |
| 44.0 | 6.4 | 6.4 | 6.4 | | | 5.5 | 5.5 | 5.5 | | | 4.7 | 4.7 | | | | | | | | |
| 46.0 | 6.4 | 6.4 | 6.4 | | | 5.5 | 5.5 | 5.5 | | | 4.7 | 4.7 | 4.7 | | | | | | | |
| 48.0 | 6.4 | 6.4 | 6.4 | | | 5.5 | 5.5 | 5.5 | | | 4.7 | 4.7 | 4.7 | | | | | | | |
| 50.0 | 6.4 | 6.4 | 6.4 | | | 5.5 | 5.5 | 5.5 | | | 4.7 | 4.7 | 4.7 | | | | | | | |
| 55.0 | 6.4 | 6.4 | 6.3 | 5.9 | | 5.5 | 5.5 | 5.5 | 5.5 | | 4.7 | 4.7 | 4.7 | 4.7 | | | | | | |
| 60.0 | 6.4 | 6.2 | 6.0 | 5.7 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | | 4.7 | 4.7 | 4.7 | 4.7 | 4.7 | | | | | |
| 65.0 | 6.1 | 5.9 | 5.8 | 5.5 | 5.4 | 5.5 | 5.5 | 5.5 | 5.5 | 5.4 | 4.7 | 4.7 | 4.7 | 4.7 | 4.7 | 4.7 | | | | |
| 70.0 | 5.5 | 5.7 | 5.8 | 5.4 | | 5.1 | 5.5 | 5.5 | 5.4 | | 4.7 | 4.7 | 4.7 | 4.7 | 4.7 | 4.7 | 4.7 | | | |
| 75.0 | 4.3 | 4.9 | 5.4 | 5.3 | | 4.0 | 4.8 | 5.2 | 5.3 | | 3.7 | 4.4 | 4.7 | 4.7 | 4.7 | 4.7 | 4.7 | 4.7 | | |
| 80.0 | 3.3 | 3.8 | | 4.2 | | 3.0 | 3.5 | 4.0 | | | 2.7 | 3.3 | 3.8 | 4.5 | | | | | | |
| 85.0 | 1.8 | 2.6 | | | | 1.9 | 2.5 | 2.9 | | | 1.7 | 2.3 | 2.7 | | | | | | | |
| 90.0 | | | | | | | | | | | | | | | | | | | | |
| θ (°) | 28 ~ 81.5 | 33 ~ 81.5 | 46 ~ 81.5 | 57 ~ 81.5 | 74 ~ 81.5 | 33 ~ 81.5 | 38 ~ 81.5 | 42 ~ 81.5 | 60 ~ 81.5 | 75 ~ 81.5 | 37 ~ 81.5 | 42 ~ 81.5 | 46 ~ 81.5 | 56 ~ 81.5 | 71 ~ 81.5 | 41 ~ 81.5 | 45 ~ 81.5 | 44 ~ 81.5 | 58 ~ 81.5 | 72 ~ 81.5 |
| 標準フック フック質量 | 12.5t 490kg | | | | | | | | | | | | | | | | | | | |
| 標準巻掛本数 | 1 | | | | | | | | | | | | | | | | | | | |