

■ 4段ESPブーム性能表 (重荷重ヘッド)

カウンタウエイト 208t、アウトリガ張出幅 9.0m、  
センタージャッキ+アシストジャッキ

4段ESPブーム+0.5m重荷重ヘッド

単位:t

ブーム長さ(m)	14.9	19.5	24.1	28.7	33.3	37.9	m
合計ブーム長さ(m)	15.4	20.0	24.6	29.2	33.8	38.4	m
作業半径 (m)	2.7						2.7
	3.0						3.0
	3.5						3.5
	4.0						4.0
	4.5	398.5					4.5
	5.0	371.9	330.0				5.0
	6.0	328.2	319.7	311.5	268.0	268.0	6.0
	7.0	293.4	285.8	278.0	268.0	266.1	200.0
	8.0	262.3	258.2	251.0	248.7	243.3	200.0
	9.0	232.8	235.8	231.0	226.7	221.5	200.0
	10.0	208.8	211.7	212.3	208.3	203.3	199.4
	11.0	189.1	191.7	192.4	192.6	187.9	184.0
	12.0	172.3	174.9	175.6	176.4	174.5	170.8
	14.0		148.2	148.9	149.6	148.9	148.4
	16.0		128.0	128.6	129.3	128.6	128.0
	18.0		74.0	112.8	113.3	112.6	112.0
	20.0			100.1	100.5	99.8	99.2
	22.0			70.5	90.0	89.2	88.6
	24.0				80.8	80.0	79.1
	26.0				61.4	71.1	70.2
28.0					63.8	62.8	
30.0					52.6	56.5	
32.0						51.2	
34.0						44.7	
36.0						30.0	
標準フック	350t×2 +アタッチメント	350t×2	350t×2	350t×2	350t×2	350t×2	

カウンタウエイト 195t、アウトリガ張出幅 9.0m、  
センタージャッキ+アシストジャッキ

4段ESPブーム+0.5m重荷重ヘッド

単位:t

ブーム長さ(m)	14.9	19.5	24.1	28.7	33.3	37.9	m
合計ブーム長さ(m)	15.4	20.0	24.6	29.2	33.8	38.4	m
作業半径 (m)	2.7	※700.0					2.7
	3.0	550.0					3.0
	3.5	465.6					3.5
	4.0	429.3	330.0				4.0
	4.5	398.5	330.0	330.0			4.5
	5.0	371.9	330.0	330.0	268.0		5.0
	6.0	328.2	319.7	311.5	268.0	268.0	6.0
	7.0	293.2	285.8	278.0	268.0	266.1	200.0
	8.0	256.7	258.2	251.0	248.7	243.3	200.0
	9.0	227.7	230.8	231.0	226.7	221.5	200.0
	10.0	204.3	207.1	207.8	208.3	203.3	199.4
	11.0	184.9	187.6	188.2	189.0	187.9	184.0
	12.0	168.7	171.1	171.7	172.5	171.8	170.8
	14.0		144.9	145.6	146.3	145.6	145.1
	16.0		125.1	125.7	126.3	125.6	125.1
	18.0		74.0	110.2	110.7	110.0	109.4
	20.0			97.8	98.1	97.4	96.8
	22.0			70.5	86.6	85.6	84.8
	24.0				76.3	75.3	74.4
	26.0				61.4	66.8	65.9
28.0					59.9	58.9	
30.0					52.6	52.9	
32.0						47.9	
34.0						43.6	
36.0						30.0	
標準フック	350t×2 +アタッチメント	350t×2	350t×2	350t×2	350t×2	350t×2	

※は旋回位置が後方限定の性能を示しています。