

■ 6段ESPブーム性能表

カウンタウエイト 208t、アウトリガ張出幅 9.0m、センタージャッキ+アシストジャッキ

6段ESPブーム

単位:t

ブーム長さ(m) 作業半径(m)	15.0	19.5	24.0	28.5	33.0	37.6	42.1	46.6	51.1	55.6	60.1	64.0	m
3.0													3.0
3.5													3.5
4.0													4.0
4.5													4.5
5.0													5.0
6.0	300.0												6.0
7.0	300.0	250.0											7.0
8.0	266.5	250.0	250.0	195.0									8.0
9.0	236.9	236.4	232.6	195.0	195.0	170.0	157.0						9.0
10.0	212.9	212.4	211.9	195.0	195.0	170.0	157.0	147.0	119.6	94.2			10.0
11.0	193.0	192.4	191.9	191.6	186.9	170.0	157.0	145.2	119.6	94.2	76.4		11.0
12.0	169.5	175.7	175.2	174.7	173.5	163.6	157.0	139.4	119.6	94.2	76.4	66.8	12.0
14.0		※151.7	※152.4	151.8	150.3	150.5	143.0	128.9	112.2	94.2	76.4	66.8	14.0
16.0		※126.9	※132.1	131.5	132.8	131.5	130.3	118.7	104.4	91.9	73.7	66.8	16.0
18.0			※116.2	115.6	117.0	115.6	114.4	109.6	97.5	86.5	69.4	64.3	18.0
20.0			※99.0	105.0	104.2	102.7	101.5	101.3	91.3	81.3	65.5	60.9	20.0
22.0			※58.9	94.6	93.7	92.2	91.9	90.7	85.7	76.6	62.0	57.6	22.0
24.0				81.9	84.8	82.9	82.5	81.1	80.6	72.3	58.8	52.9	24.0
26.0				57.6	75.9	74.7	73.6	72.2	72.8	68.4	55.9	48.8	26.0
28.0					67.5	67.3	66.2	64.7	65.3	64.8	53.1	45.3	28.0
30.0					51.2	61.1	59.9	59.2	59.0	59.8	50.6	42.1	30.0
32.0						55.8	54.5	55.3	53.6	54.4	48.3	39.4	32.0
34.0							44.7	49.9	50.6	49.4	49.7	46.2	34.0
36.0								45.8	46.5	47.0	45.5	44.3	36.0
38.0								38.8	42.9	43.5	41.9	42.5	38.0
40.0								27.9	39.8	40.3	39.0	30.9	40.0
42.0									35.5	37.5	37.0	37.1	42.0
44.0									28.2	34.9	35.2	34.4	44.0
46.0										32.0	33.1	32.1	46.0
48.0										26.6	31.0	30.0	48.0
50.0											29.1	28.0	50.0
52.0											23.3	26.3	52.0
54.0												24.7	54.0
56.0												20.8	56.0
58.0												12.5	58.0
60.0													60.0
62.0													62.0
標準フック	350t+ アタッチメント	350t+ アタッチメント	350t+ アタッチメント	350t	350t	350t	350t	350t	350t	350t	150t	150t	

(※は標準フックが350t)

カウンタウエイト 164t、アウトリガ張出幅 9.0m、センタージャッキ+アシストジャッキ

6段ESPブーム

単位:t

ブーム長さ(m) 作業半径(m)	15.0	19.5	24.0	28.5	33.0	37.6	42.1	46.6	51.1	55.6	60.1	64.0	m
3.0	300.0	250.0											3.0
3.5	300.0	250.0	250.0										3.5
4.0	300.0	250.0	250.0										4.0
4.5	300.0	250.0	250.0	195.0									4.5
5.0	300.0	250.0	250.0	195.0									5.0
6.0	300.0	250.0	250.0	195.0	195.0								6.0
7.0	282.5	250.0	250.0	195.0	195.0	170.0							7.0
8.0	247.7	247.2	246.7	195.0	195.0	170.0	157.0						8.0
9.0	220.0	219.6	219.1	195.0	195.0	170.0	157.0	147.0	119.6				9.0
10.0	197.6	197.1	196.6	195.0	195.0	170.0	157.0	147.0	119.6	94.2			10.0
11.0	179.0	178.4	177.9	177.6	176.3	170.0	157.0	145.2	119.6	94.2	76.4		11.0
12.0	163.4	※165.5	※166.2	165.6	164.2	163.6	157.0	139.4	119.6	94.2	76.4	66.8	12.0
14.0		※140.6	※141.2	140.7	142.1	140.7	139.5	128.9	112.2	94.2	76.4	66.8	14.0
16.0		※121.7	※122.3	124.0	123.2	121.7	120.5	118.7	104.4	91.9	73.7	66.8	16.0
18.0			※103.4	105.6	104.5	103.4	102.3	100.8	97.5	86.5	69.4	64.3	18.0
20.0			※90.9	90.9	89.8	88.7	87.6	86.1	86.8	81.3	65.5	60.9	20.0
22.0			※58.9	79.4	78.3	77.2	76.1	74.7	75.3	76.3	62.0	57.6	22.0
24.0				70.3	69.1	68.0	66.9	67.8	66.7	67.0	58.8	52.9	24.0
26.0				57.6	61.6	60.5	59.4	60.2	61.0	59.4	55.9	48.8	26.0
28.0					55.5	54.3	53.1	53.9	54.7	53.1	53.1	45.3	28.0
30.0					50.4	49.0	47.8	48.6	49.3	49.1	49.2	42.1	30.0
32.0						44.6	43.3	44.0	44.9	45.4	44.6	39.4	32.0
34.0						40.8	39.4	40.1	42.2	41.4	40.6	36.9	34.0
36.0							36.6	36.7	38.9	37.9	37.0	34.7	36.0
38.0							35.1	33.9	35.8	34.8	34.0	32.7	38.0
40.0								27.9	32.1	33.1	32.1	30.9	40.0
42.0									30.5	30.8	29.7	28.8	42.0
44.0								28.2	28.6	27.5	26.6	26.5	44.0
46.0									26.8	25.6	24.6	24.5	46.0
48.0									25.1	23.8	22.8	22.7	48.0
50.0										22.3	21.2	21.1	50.0
52.0										20.9	19.7	19.6	52.0
54.0											18.4	18.3	54.0
56.0											17.2	17.0	56.0
58.0											12.5	15.9	58.0
60.0												14.9	60.0
62.0												10.3	62.0
標準フック	350t+ アタッチメント	350t+ アタッチメント	350t+ アタッチメント	350t	350t	350t	350t	350t	350t	350t	150t	150t	

(※は標準フックが350t)