

■ 6段ESPブーム+フルオートラフィングジブ性能表

カウンタウエイト 164t、アウトリガ張出幅 9.0m、アシストジャッキ

6段ESPブーム55.6m+1.7m+フルオートラフィングジブ

単位:t

フルオートラフィングジブ長さ (m)	11.1	11.1	11.1	11.1	19.1	19.1	19.1	19.1	27.1	27.1	27.1	27.1	35.1	35.1	35.1	35.1	m	
ジブオフセット(°)	0	15	30	40	0	15	30	40	0	15	30	40	0	15	30	40	°	
16.0	48.6				27.2												16.0	
18.0	47.2	35.6			26.2				15.5								18.0	
20.0	44.6	33.5	25.1	22.0	24.3	15.9			14.7				8.6				20.0	
22.0	42.2	31.5	24.1	21.3	22.7	15.1			13.4				8.6				22.0	
24.0	39.9	29.8	23.2	20.6	21.2	14.3	11.0		12.4	7.9			8.6				24.0	
26.0	37.4	28.2	22.3	20.1	20.0	13.7	10.6	9.3	11.5	7.5			8.0				26.0	
28.0	34.9	26.8	21.5	19.5	18.8	13.1	10.3	9.1	10.7	7.1			7.4	4.7			28.0	
30.0	32.8	25.5	20.8	19.0	17.6	12.5	9.9	8.8	10.0	6.8	5.1		6.9	4.5			30.0	
32.0	30.9	24.3	20.1	18.5	16.6	12.0	9.6	8.6	9.3	6.4	4.9		6.4	4.2			32.0	
34.0	29.2	23.2	19.5	18.1	15.7	11.5	9.3	8.4	8.7	6.1	4.7	4.1	6.0	4.0			34.0	
36.0	27.6	22.3	19.0	17.7	14.8	11.1	9.1	8.3	8.2	5.9	4.6	4.0	5.6	3.8	2.8		36.0	
38.0	26.2	21.3	18.4	17.4	14.1	10.6	8.8	8.1	7.7	5.6	4.4	3.9	5.2	3.6	2.7		38.0	
40.0	23.9	20.5	17.9	17.1	13.4	10.3	8.6	8.0	7.3	5.4	4.3	3.8	4.9	3.4	2.6	2.2	40.0	
42.0	21.5	19.7	17.5	16.8	12.7	9.9	8.4	7.8	6.9	5.1	4.1	3.7	4.6	3.3	2.5	2.1	42.0	
44.0	19.2	19.0	17.1	16.5	12.1	9.6	8.2	7.7	6.6	4.9	4.0	3.6	4.3	3.1	2.4	2.1	44.0	
46.0	17.2	18.0	16.7	16.3	11.6	9.3	8.1	7.6	6.2	4.7	3.9	3.5	4.1	3.0	2.3	2.0	46.0	
48.0	15.4	16.1	16.4	16.1	11.1	9.0	7.9	7.5	5.9	4.6	3.8	3.4	3.9	2.8	2.2	1.9	48.0	
50.0	13.7	14.3	14.7		10.6	8.7	7.7	7.4	5.6	4.4	3.7	3.4	3.7	2.7	2.1	1.9	50.0	
55.0	10.1	10.6	10.8		9.6	8.1	7.4	7.3	5.0	4.0	3.5	3.2	3.2	2.4	1.9	1.7	55.0	
60.0	7.2	7.5			8.7	7.7	7.2		4.5	3.7	3.3	3.1	2.8	2.2	1.8	1.6	60.0	
65.0	4.7				6.9	7.3			4.1	3.5	3.2	3.1	2.5	2.0	1.6	1.5	65.0	
70.0					4.6	5.0			3.7	3.3	3.1		2.2	1.8	1.5	1.4	70.0	
75.0									3.4	3.1			1.9	1.6	1.4		75.0	
80.0									3.2				1.7	1.5	1.4		80.0	
ブーム伸縮状態 (伸縮割合) (%)	1	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	1
	2	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	2
	3	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	3
	4	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	4
	5	45	45	45	45	45	45	45	45	45	45	45	45	45	45	45	45	5
ID	31	31	31	31	31	31	31	31	31	31	31	31	31	31	31	31	31	ID
ブーム角度の範囲 無負荷時(°)	14~82	30~82	39~82	50~82	23~82	25~82	44~82	51~82	18~82	31~82	40~82	48~82	32~82	36~82	37~82	52~82	°	
標準巻掛本数	5	5	5	5	3	3	3	3	2	2	2	2	1	1	1	1		
標準フック	80t	80t	80t	80t	80t	80t	80t	80t	25t	25t	25t	25t	12.5t	12.5t	12.5t	12.5t		

カウンタウエイト 164t、アウトリガ張出幅 9.0m、アシストジャッキ

6段ESPブーム60.1m+1.7m+フルオートラフィングジブ

単位:t

フルオートラフィングジブ長さ (m)	11.1	11.1	11.1	11.1	19.1	19.1	19.1	19.1	27.1	27.1	27.1	27.1	35.1	35.1	35.1	35.1	m	
ジブオフセット(°)	0	15	30	40	0	15	30	40	0	15	30	40	0	15	30	40	°	
16.0	39.6																16.0	
18.0	37.5	32.8			24.9				14.6								18.0	
20.0	35.3	31.0			24.8				14.6				8.3				20.0	
22.0	33.3	29.3	24.3	21.4	23.2	15.2			13.8				8.3				22.0	
24.0	31.4	27.8	23.4	20.8	21.7	14.5			12.7				8.3				24.0	
26.0	29.6	26.3	22.6	20.2	20.5	13.8	10.7		11.8	7.5			8.1				26.0	
28.0	28.0	24.9	21.9	19.7	19.3	13.2	10.3	9.1	11.0	7.1			7.6				28.0	
30.0	26.5	23.6	21.2	19.2	18.2	12.7	10.0	8.9	10.3	6.8			7.1	4.5			30.0	
32.0	25.1	22.5	20.5	18.8	17.2	12.2	9.7	8.6	9.6	6.5	5.0		6.6	4.3			32.0	
34.0	23.7	21.4	19.9	18.4	16.3	11.7	9.4	8.5	9.0	6.2	4.8	4.1	6.2	4.1			34.0	
36.0	22.5	20.4	19.1	18.0	15.4	11.3	9.2	8.3	8.5	5.9	4.6	4.0	5.8	3.9			36.0	
38.0	21.4	19.4	18.3	17.6	14.6	10.9	8.9	8.2	8.0	5.7	4.5	3.9	5.4	3.7	2.7		38.0	
40.0	20.3	18.6	17.6	17.3	13.9	10.5	8.7	8.0	7.6	5.4	4.3	3.8	5.1	3.5	2.6		40.0	
42.0	19.4	17.8	16.9	16.6	13.3	10.1	8.5	7.9	7.2	5.2	4.2	3.7	4.8	3.3	2.5	2.1	42.0	
44.0	18.5	17.0	16.2	16.0	12.7	9.8	8.3	7.8	6.8	5.0	4.1	3.6	4.5	3.2	2.4	2.1	44.0	
46.0	17.7	16.3	15.6	15.5	12.1	9.5	8.2	7.6	6.5	4.8	3.9	3.5	4.3	3.0	2.3	2.0	46.0	
48.0	15.8	15.7	15.1	15.0	11.6	9.2	8.0	7.5	6.2	4.7	3.8	3.5	4.0	2.9	2.2	1.9	48.0	
50.0	14.1	14.8	14.6	14.5	11.1	8.9	7.8	7.4	5.9	4.5	3.7	3.4	3.8	2.8	2.2	1.9	50.0	
55.0	10.5	11.1	11.4		10.1	8.3	7.5	7.3	5.3	4.1	3.5	3.2	3.3	2.5	2.0	1.7	55.0	
60.0	7.6	8.0	8.1		9.2	7.8	7.3	7.2	4.7	3.8	3.3	3.1	2.9	2.2	1.8	1.6	60.0	
65.0	5.0	5.3			7.2	7.5	7.1		4.3	3.6	3.2	3.1	2.6	2.0	1.7	1.5	65.0	
70.0	3.0				4.9	5.4			3.9	3.3	3.1		2.3	1.8	1.6	1.4	70.0	
75.0					3.0	3.3			3.6	3.2	3.0		2.1	1.7	1.5	1.4	75.0	
80.0									3.3	3.1			1.8	1.5	1.4		80.0	
ブーム伸縮状態 (伸縮割合) (%)	1	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	1
	2	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	2
	3	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	3
	4	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	4
	5	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	5
ID	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	ID
ブーム角度の範囲 無負荷時(°)	11~82	28~82	38~82	52~82	22~82	23~82	42~82	49~82	28~82	30~82	39~82	52~82	37~82	41~82	43~82	50~82	°	
標準巻掛本数	5	5	5	5	3	3	3	3	2	2	2	2	1	1	1	1		
標準フック	80t	80t	80t	80t	80t	80t	80t	80t	25t	25t	25t	25t	12.5t	12.5t	12.5t	12.5t		