

■ ブーム性能表

カウンタウエイト 71t、アウトリガ張出幅 8.3m
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※13.2	13.2	17.4	21.6	25.8	30.0	34.1	38.3	42.5	46.7	50.9	55.0	59.2	63.4	68.0	m
2.5	220.0	199.1														2.5
3.0	180.0	178.7	117.7	110.0	94.2											3.0
3.5	169.5	161.7	117.7	110.0	94.2	86.2										3.5
4.0	160.0	147.3	117.7	110.0	94.2	86.2										4.0
4.5	150.5	134.9	117.7	110.0	94.2	86.2	69.9									4.5
5.0	135.5	124.2	117.7	110.0	94.2	86.2	69.9	54.5								5.0
6.0	112.5	106.7	107.4	106.2	94.2	79.5	69.9	54.5	43.5							6.0
7.0	96.0	93.0	93.7	94.2	93.1	77.5	66.5	54.5	43.5	34.5						7.0
8.0	83.2	82.0	82.7	83.2	82.1	77.5	61.0	54.5	43.5	34.5	28.5					8.0
9.0	73.1	73.1	73.7	74.2	73.1	74.0	58.0	52.6	43.5	34.5	28.5	23.0				9.0
10.0	64.9	64.9	66.0	65.9	66.3	65.7	58.0	48.9	42.6	34.5	28.5	23.0	18.8			10.0
11.0			59.3	59.6	59.9	58.9	57.6	45.6	40.4	34.5	28.5	23.0	18.8	15.0		11.0
12.0			53.6	54.4	54.2	53.2	54.1	43.4	39.2	33.6	28.5	23.0	18.8	15.0	13.8	12.0
14.0			44.8	45.5	45.3	45.8	45.2	40.5	36.0	31.5	27.9	23.0	18.8	15.0	13.8	14.0
16.0				38.9	39.4	39.1	38.5	37.9	32.3	29.1	25.7	22.8	18.8	15.0	13.8	16.0
18.0				33.5	34.1	33.8	33.3	34.0	29.3	26.8	23.8	21.1	18.8	15.0	13.4	18.0
20.0					29.4	29.1	29.9	29.3	26.7	24.6	22.0	19.9	17.8	15.0	13.1	20.0
22.0					25.7	26.5	26.2	25.5	24.5	22.7	20.5	18.6	16.6	14.9	12.8	22.0
24.0						23.5	23.1	22.5	21.8	21.0	19.1	17.4	15.6	14.0	12.5	24.0
26.0						21.0	20.6	19.9	19.3	19.2	17.9	16.4	14.7	13.2	12.3	26.0
28.0							18.5	17.8	17.2	17.8	16.8	15.4	13.8	12.5	11.5	28.0
30.0							16.7	16.0	16.2	16.0	15.3	14.5	13.1	11.8	10.7	30.0
32.0								14.4	15.1	14.4	13.8	13.7	12.4	11.2	10.0	32.0
34.0								13.1	13.7	13.1	12.6	13.0	11.8	10.6	9.4	34.0
36.0									12.5	11.9	12.1	12.1	11.3	10.1	8.8	36.0
38.0									11.5	11.1	11.2	11.0	10.8	9.7	8.3	38.0
40.0										10.7	10.2	10.0	10.3	9.2	7.8	40.0
42.0										10.0	9.4	9.2	9.4	8.8	7.4	42.0
44.0										8.3	8.6	8.7	8.7	8.5	6.9	44.0
46.0											8.2	8.3	7.9	7.7	6.5	46.0
48.0											7.9	7.7	7.4	7.3	6.2	48.0
50.0												7.1	7.1	6.7	5.8	50.0
52.0												6.6	6.6	6.1	5.5	52.0
54.0													6.1	5.6	5.2	54.0
56.0													5.7	5.1	4.9	56.0
58.0														4.7	4.6	58.0
60.0														4.3	4.2	60.0
62.0															3.8	62.0
64.0															3.5	64.0
標準フック	125t×2	125t×2	125t	125t	95t	95t	95t	95t	95t	95t	95t	28t	28t	28t	28t	

※は旋回位置が後方限定の性能を示しています。

カウンタウエイト 47t、アウトリガ張出幅 8.3m
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※13.2	13.2	17.4	21.6	25.8	30.0	34.1	38.3	42.5	46.7	50.9	55.0	59.2	63.4	68.0	m
2.5	220.0	190.8														2.5
3.0	180.0	170.6	117.7	110.0	94.2											3.0
3.5	169.5	153.8	117.7	110.0	94.2	86.2										3.5
4.0	154.0	139.5	117.7	110.0	94.2	86.2										4.0
4.5	136.9	127.3	117.7	110.0	94.2	86.2	69.9									4.5
5.0	123.1	116.8	117.6	110.0	94.2	86.2	69.9	54.5								5.0
6.0	102.0	99.7	100.5	99.2	94.2	79.5	69.9	54.5	43.5							6.0
7.0	86.2	86.2	86.9	87.4	86.4	77.5	66.5	54.5	43.5	34.5						7.0
8.0	74.2	74.2	75.5	75.4	75.7	75.2	61.0	54.5	43.5	34.5	28.5					8.0
9.0	64.9	64.9	66.2	66.5	66.4	65.8	58.0	52.6	43.5	34.5	28.5	23.0				9.0
10.0	57.5	57.5	58.7	59.5	59.3	58.3	58.0	48.9	42.6	34.5	28.5	23.0	18.8			10.0
11.0			52.1	53.2	52.9	53.6	52.8	45.6	40.4	34.5	28.5	23.0	18.8	15.0		11.0
12.0			45.7	46.8	47.4	47.1	46.3	43.4	39.2	33.6	28.5	23.0	18.8	15.0	13.8	12.0
14.0			36.3	37.3	37.9	37.6	38.5	37.9	36.0	31.5	27.9	23.0	18.8	15.0	13.8	14.0
16.0				30.6	31.2	32.1	31.8	31.1	30.4	29.1	25.7	22.8	18.8	15.0	13.8	16.0
18.0				26.2	27.2	27.1	26.8	26.2	25.5	25.4	23.8	21.1	18.8	15.0	13.4	18.0
20.0					23.4	23.3	23.0	22.3	21.6	22.4	21.6	19.9	17.8	15.0	13.1	20.0
22.0					20.3	20.1	19.8	19.1	19.8	19.2	18.5	18.6	16.6	14.9	12.8	22.0
24.0						17.6	17.2	16.6	17.3	16.6	16.1	16.5	15.6	14.0	12.5	24.0
26.0						15.5	15.1	14.4	15.1	14.7	14.9	14.7	14.6	13.2	12.3	26.0
28.0							13.4	12.7	13.4	13.9	13.2	13.2	13.3	12.5	11.5	28.0
30.0								11.9	11.2	11.9	12.5	12.2	12.1	11.7	11.8	30.0
32.0									9.9	10.6	11.2	11.3	10.8	10.9	10.5	32.0
34.0									8.9	9.7	10.1	10.2	10.0	9.8	9.3	34.0
36.0										9.2	9.5	9.3	9.2	8.8	8.3	36.0
38.0										8.8	8.9	8.6	8.3	7.9	7.5	38.0
40.0											8.1	7.8	7.5	7.2	6.7	40.0
42.0											7.4	7.1	6.8	6.5	5.9	42.0
44.0											6.8	6.5	6.2	5.8	5.3	44.0
46.0												6.0	5.6	5.2	4.7	46.0
48.0												5.5	5.1	4.7	4.1	48.0
50.0													4.6	4.2	3.6	50.0
52.0													3.6	3.7	3.2	52.0
54.0														3.3	2.8	54.0
56.0														2.9	2.4	56.0
58.0															2.0	58.0
60.0															1.7	60.0
62.0																62.0
64.0																64.0
標準フック	125t×2	125t×2	125t	125t	95t	95t	95t	95t	95t	95t	95t	28t	28t	28t	28t	

※は旋回位置が後方限定の性能を示しています。