

■ ブーム性能表

カウンタウエイト 12t、アウトリガ張出幅 8.3m
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※13.2	13.2	17.4	21.6	25.8	30.0	34.1	38.3	42.5	46.7	50.9	55.0	59.2	63.4	68.0	m
2.5	207.8	176.9														2.5
3.0	174.9	156.9	117.7	110.0	94.2											3.0
3.5	150.6	140.2	117.7	110.0	94.2	86.2										3.5
4.0	131.9	126.2	117.7	110.0	94.2	86.2										4.0
4.5	116.6	114.4	115.2	110.0	94.2	86.2	69.9									4.5
5.0	103.9	103.9	104.8	103.5	94.2	86.2	69.9	54.5								5.0
6.0	85.0	85.0	86.4	86.8	85.2	79.5	69.9	54.5	43.5							6.0
7.0	71.2	66.3	68.4	69.0	68.8	67.9	66.5	54.5	43.5	34.5						7.0
8.0	53.3	52.4	54.3	55.6	56.4	56.1	55.1	54.2	43.5	34.5	28.5					8.0
9.0	42.0	42.0	43.9	45.4	46.3	46.0	47.2	43.8	43.5	34.5	28.5	23.0				9.0
10.0	34.1	34.1	35.9	38.8	39.4	39.3	38.9	38.0	37.1	34.5	28.5	23.0	18.8			10.0
11.0			31.3	32.7	33.3	33.1	32.8	32.0	31.1	31.0	28.5	23.0	18.8	15.0		11.0
12.0			26.7	28.1	28.6	28.5	28.1	27.4	28.3	27.1	26.6	23.0	18.8	15.0	13.8	12.0
14.0			20.1	21.5	21.9	21.8	21.5	20.7	21.6	21.9	21.4	20.8	18.8	15.0	13.8	14.0
16.0				17.1	18.1	17.2	17.7	17.4	18.5	18.6	18.3	17.3	16.7	15.0	13.8	16.0
18.0				13.7	14.7	14.6	15.4	15.4	15.4	15.1	14.9	14.6	14.1	13.5	13.4	18.0
20.0					12.1	12.5	12.8	12.7	12.8	12.5	12.2	11.9	11.5	11.0	10.9	20.0
22.0					10.1	10.4	10.8	10.7	10.7	10.5	10.2	9.9	9.5	9.0	9.0	22.0
24.0						8.9	9.2	9.1	9.1	8.9	8.6	8.3	7.9	7.4	7.4	24.0
26.0						7.6	7.8	7.8	7.8	7.5	7.3	7.0	6.6	6.1	6.1	26.0
28.0							6.8	6.7	6.7	6.4	6.2	5.9	5.5	5.0	5.0	28.0
30.0							5.9	5.8	5.8	5.5	5.3	5.0	4.6	4.1	4.1	30.0
32.0								5.0	5.0	4.7	4.5	4.2	3.8	3.3	3.3	32.0
34.0								4.3	4.3	4.0	3.8	3.5	3.1	2.6		34.0
36.0									3.7	3.4	3.2	2.9	2.5			36.0
38.0									3.2	2.9	2.7	2.4	2.0			38.0
40.0										2.5	2.2	1.9				40.0
42.0										2.1	1.8	1.4				42.0
44.0										1.7	1.4					44.0
46.0											1.1					46.0
標準フック	125t×2	125t×2	125t	125t	95t	95t	95t	95t	95t	95t	95t	28t	28t	28t	28t	

※は旋回位置が後方限定の性能を示しています。

カウンタウエイト 0t、アウトリガ張出幅 8.3m
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※13.2	13.2	17.4	21.6	25.8	30.0	34.1	38.3	42.5	46.7	50.9	55.0	59.2	63.4	68.0	m
2.5	196.7	171.5														2.5
3.0	165.4	151.5	117.7	110.0	94.2											3.0
3.5	142.3	134.9	117.7	110.0	94.2	86.2										3.5
4.0	123.8	121.0	117.7	110.0	94.2	86.2										4.0
4.5	109.0	109.0	109.8	108.5	94.2	86.2	69.9									4.5
5.0	97.1	97.1	97.9	96.6	94.2	86.2	69.9	54.5								5.0
6.0	77.7	71.9	74.3	75.0	74.8	73.7	69.9	54.5	43.5							6.0
7.0	52.8	52.8	55.5	57.2	58.1	57.7	56.6	54.5	43.5	34.5						7.0
8.0	39.0	39.0	41.2	44.1	45.4	45.3	44.9	43.5	41.3	34.5	28.5					8.0
9.0	30.2	30.2	33.7	35.4	36.0	35.9	35.5	34.5	33.5	33.5	28.5	23.0				9.0
10.0	24.2	23.8	27.3	28.9	29.4	29.3	29.0	28.1	29.1	27.1	27.2	23.0	18.8			10.0
11.0			22.2	23.8	24.8	24.3	23.9	23.4	24.1	24.3	22.6	22.7	18.8	15.0		11.0
12.0			18.4	20.1	21.4	20.4	21.8	21.9	22.4	21.4	19.9	19.2	18.8	15.0	13.8	12.0
14.0			13.1	14.7	15.8	16.3	16.7	16.7	16.4	16.4	16.1	15.8	15.0	14.6	13.8	14.0
16.0				11.1	12.2	12.6	13.0	12.9	13.0	12.7	12.4	12.1	11.6	11.0	11.0	16.0
18.0				8.6	9.6	10.0	10.3	10.3	10.3	10.0	9.8	9.5	9.0	8.4	8.4	18.0
20.0					7.6	8.0	8.3	8.3	8.3	8.1	7.8	7.5	7.0	6.5	6.5	20.0
22.0					6.2	6.5	6.8	6.8	6.8	6.5	6.3	6.0	5.5	5.0	5.0	22.0
24.0						5.3	5.6	5.5	5.6	5.3	5.0	4.8	4.3	3.8		24.0
26.0						4.3	4.6	4.5	4.6	4.3	4.0	3.8	3.3			26.0
28.0							3.8	3.7	3.7	3.5	3.2	2.9				28.0
30.0							3.1	3.0	3.0	2.8	2.5	2.2				30.0
32.0								2.5	2.4	2.2	1.9					32.0
34.0								2.0	1.9	1.7						34.0
36.0									1.5	1.2						36.0
38.0										1.1						38.0
標準フック	125t×2	125t×2	125t	125t	95t	95t	95t	95t	95t	95t	95t	28t	28t	28t	28t	

※は旋回位置が後方限定の性能を示しています。