

■ ブーム+ラフィングジブ(LJ)定格総荷重表

カウンタウエイト 138t、アウトリガ張出幅 8.5m
 ブーム+2.5m+58.0m(ライト)LJ

単位:t

ブーム長さ	15.0m			25.1m			35.3m			45.4m			55.6m		
ブーム起伏角 作業半径(m)	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°
22.0	20.9														
24.0	19.9			16.8											
26.0	18.8			16.6			14.5								
28.0	17.6			16.3			14.4								
30.0	16.7			16.1			14.2						9.4		
32.0	15.7	16.8		15.4			14.1						9.3		4.9
34.0	14.8	15.8		14.7			13.8						9.3		4.9
36.0	14.0	15.0		14.0	15.1		13.5						9.2		4.8
38.0	13.3	14.1		13.3	14.5		13.1	13.9					9.1		4.8
40.0	12.6	13.4	14.1	12.7	13.9		12.6	13.3					9.1		4.7
42.0	12.0	12.7	13.4	12.1	13.2		12.2	12.7					9.0		4.6
44.0	11.4	12.1	12.7	11.5	12.6	12.9	11.7	12.2					9.0	8.9	4.6
46.0	10.8	11.5	12.0	11.0	12.0	12.4	11.3	11.7					8.9	8.8	4.6
48.0	10.3	10.9	11.4	10.5	11.5	11.9	10.8	11.2					8.9	8.5	4.6
50.0	9.8	10.4	10.9	10.0	10.9	11.5	10.4	10.8	9.4				8.9	8.0	4.6
54.0	9.0	9.5	9.9	9.2	10.0	10.7	9.6	9.8	8.3				8.2	7.1	4.5
58.0		8.7	9.1		9.1	9.8	8.8	8.9	7.4				7.5	6.4	5.6
62.0					8.4	9.0		8.1	6.6					5.7	5.0
66.0									6.0					5.2	4.4
70.0									5.4					3.9	2.0
74.0														3.5	
標準フック	35t			35t			35t			12.2t			12.2t		

カウンタウエイト 138t、アウトリガ張出幅 8.5m
 ブーム+2.5m+64.0m(ライト)LJ

単位:t

ブーム長さ	15.0m			25.1m			35.3m			45.4m			55.6m	
ブーム起伏角 作業半径(m)	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°
24.0	16.5													
26.0	15.6			14.6										
28.0	14.8			14.1										
30.0	13.9			13.5			12.0							
32.0	13.1			12.9			11.7						7.9	
34.0	12.4	13.2		12.3			11.4						7.8	4.0
36.0	11.7	12.5		11.7			11.0						7.8	4.0
38.0	11.1	11.8		11.1	12.2		10.7						7.7	3.9
40.0	10.5	11.2		10.6	11.6		10.3						7.7	3.9
42.0	9.9	10.6	11.1	10.1	11.0		9.9	10.6					7.6	3.9
44.0	9.4	10.0	10.5	9.6	10.5		9.5	10.1					7.6	3.8
46.0	9.0	9.5	10.0	9.1	10.0		9.1	9.7					7.5	7.6
48.0	8.5	9.0	9.5	8.7	9.5	10.3	8.8	9.3					7.5	7.5
50.0	8.1	8.6	9.0	8.3	9.1	9.8	8.4	9.0					7.5	7.4
54.0	7.4	7.8	8.2	7.6	8.3	8.9	7.7	8.3	7.1				7.1	6.8
58.0	6.7	7.1	7.4	6.9	7.5	8.1	7.1	7.7	6.6				6.8	6.2
62.0		6.5	6.8	6.4	6.9	7.4	6.5	7.2	6.1				6.4	5.6
66.0			6.2		6.3	6.8		6.7	5.7				5.0	4.4
70.0						6.2		6.2	5.3				4.5	3.6
74.0									4.8				4.1	3.3
78.0														2.9
標準フック	35t			35t			12.2t			12.2t			12.2t	