

ヘビーリフトジブ

■定格総荷重表

■13.6mブーム+4.35m+12mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
6.0(m)	84.0				
7.0	83.9				
8.0	82.6	79.3			
9.0	81.4	75.3			
10.0	76.6	71.4	60.9		
11.0	71.0	67.5	58.2		
12.0	65.2	64.1	55.8	43.2	
14.0	55.8	58.2	51.6	40.9	31.9
16.0	48.6	50.9	48.2	39.1	31.2
18.0	42.8	43.9	44.6	37.7	30.9
20.0	37.7	38.3	38.8	36.7	
22.0	33.2	33.7	34.0	34.3	
24.0	29.5	29.8	30.0		
26.0	26.3	26.5			
θ(°)	10~83	20~83	30~83	45~83	60~83
標準フック	150 ton				
フック重量	1850 kg				
巻掛本数	8本				

(単位: ton)

■18.15mブーム+4.35m+12mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
7.0(m)	77.0				
8.0	77.0				
9.0	77.0	77.0			
10.0	75.5	75.3			
11.0	69.7	70.1	60.7		
12.0	64.4	65.1	58.4		
14.0	55.3	56.7	54.4	43.5	34.0
16.0	47.8	49.0	50.1	41.7	33.2
18.0	40.9	41.9	42.9	40.1	32.5
20.0	35.5	36.3	37.0	37.9	32.4
22.0	31.0	31.6	32.3	32.9	
24.0	27.2	27.8	28.3	28.7	
26.0	24.1	24.5	24.9		
28.0	21.4	21.7	21.9		
30.0	19.0	19.2			
32.0	12.4				
θ(°)	10~83	20~83	30~83	45~83	60~83
標準フック	150 ton				
フック重量	1850 kg				
巻掛本数	8本				

(単位: ton)

■22.7mブーム+4.35m+12mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
8.0(m)	64.0				
9.0	64.0				
10.0	64.0	64.0			
11.0	64.0	64.0	64.0		
12.0	60.3	61.6	61.8		
14.0	51.8	53.3	54.4	46.9	
16.0	44.8	46.3	47.7	45.0	35.5
18.0	39.2	40.4	41.5	42.9	34.8
20.0	33.7	34.7	35.7	36.8	34.4
22.0	29.2	30.1	30.9	31.8	32.2
24.0	25.5	26.2	26.9	27.6	
26.0	22.3	23.0	23.5	24.0	
28.0	19.6	20.2	20.6	20.9	
30.0	17.3	17.7	18.0		
32.0	15.3	15.6	15.8		
34.0	13.5	13.7			
36.0	9.6				
θ(°)	10~83	20~83	30~83	45~83	60~83
標準フック	65 ton				
フック重量	1000 kg				
巻掛本数	6本				

(単位: ton)

■31.8mブーム+4.35m+12mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
9.0(m)	40.0				
10.0	39.5				
11.0	38.8	34.9			
12.0	38.2	34.4			
14.0	37.0	33.6	30.6		
16.0	36.0	32.8	30.0	26.2	
18.0	33.3	32.2	29.6	26.0	22.6
20.0	29.9	30.9	29.2	25.8	22.6
22.0	26.6	27.5	28.5	25.7	22.6
24.0	23.7	24.5	25.3	25.7	22.6
26.0	21.3	22.0	22.7	23.6	22.6
28.0	19.2	19.8	20.4	21.1	
30.0	17.3	17.8	18.3	18.9	
32.0	15.2	15.7	16.1	16.5	
34.0	13.4	13.9	14.2	14.4	
36.0	11.8	12.2	12.4		
38.0	10.4	10.6	10.8		
40.0	9.1	9.3	9.4		
45.0	4.6				
θ(°)	10~83	20~83	30~83	45~83	60~83
標準フック	65 ton				
フック重量	1000 kg				
巻掛本数	4本				

(単位: ton)

■13.6mブーム+4.35m+21mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
9.0(m)	55.5				
10.0	54.7				
11.0	53.6				
12.0	52.6				
14.0	48.7	41.4			
16.0	43.5	37.7	33.0		
18.0	39.4	34.6	30.7		
20.0	35.9	32.0	28.7	22.9	
22.0	33.0	29.9	27.0	21.9	17.2
24.0	30.6	28.0	25.6	21.0	16.8
26.0	28.1	26.4	24.3	20.3	16.5
28.0	25.1	25.0	23.2	19.7	
30.0	22.6	23.0	22.4	19.4	
32.0	20.4	20.7	21.0		
34.0	18.6	18.8	18.9		
36.0	16.9				
θ(°)	10~83	20~83	30~83	45~83	60~83
標準フック	65 ton				
フック重量	1000 kg				
巻掛本数	6本				

(単位: ton)

■18.15mブーム+4.35m+21mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
10.0(m)	53.0				
11.0	53.0				
12.0	53.0				
14.0	51.8	43.3			
16.0	47.2	39.7	34.3		
18.0	42.8	36.6	32.0		
20.0	37.9	34.0	30.2	24.2	
22.0	33.4	31.8	28.5	23.2	18.1
24.0	29.6	29.9	27.1	22.3	17.7
26.0	26.3	27.3	25.8	21.6	17.4
28.0	23.5	24.2	24.7	21.0	17.2
30.0	20.9	21.6	22.1	20.5	
32.0	18.8	19.3	19.8	20.1	
34.0	16.9	17.4	17.7	18.1	
36.0	15.3	15.6	15.9		
38.0	13.9	14.1	14.3		
40.0	12.1	12.7			
θ(°)	10~83	20~83	30~83	45~83	60~83
標準フック	65 ton				
フック重量	1000 kg				
巻掛本数	6本				

(単位: ton)

■22.7mブーム+4.35m+21mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
11.0(m)	44.0				
12.0	44.0				
14.0	44.0				
16.0	44.0	43.9			
18.0	42.3	40.6	34.7		
20.0	36.7	37.7	32.7		
22.0	32.1	33.7	31.0	25.2	
24.0	28.3	29.6	29.4	24.3	19.1
26.0	25.0	26.2	27.3	23.5	18.7
28.0	22.2	23.2	24.1	22.8	18.5
30.0	19.8	20.6	21.3	22.2	18.3
32.0	17.6	18.3	19.0	19.7	18.2
34.0	15.8	16.4	16.9	17.5	
36.0	14.1	14.6	15.1	15.5	
38.0	12.7	13.1	13.4		
40.0	11.4	11.7	12.0		
45.0	7.0				
θ(°)	10~83	20~83	30~83	45~83	60~83
標準フック	65 ton				
フック重量	1000 kg				
巻掛本数	4本				

(単位: ton)

■31.8mブーム+4.35m+21mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
14.0(m)	27.0				
16.0	27.0	25.0			
18.0	27.0	24.1			
20.0	26.0	23.4	21.1		
22.0	25.1	22.8	20.6		
24.0	24.3	22.2	20.1	17.2	
26.0	22.7	21.7	19.7	17.0	14.3
28.0	20.9	21.2	19.4	16.8	14.2
30.0	18.9	19.9	19.1	16.6	14.2
32.0	17.0	17.9	18.7	16.6	14.2
34.0	15.2	15.9	16.6	16.5	14.2
36.0	13.5	14.2	14.8	15.5	14.2
38.0	12.1	12.7	13.2	13.8	
40.0	10.7	11.4	11.8	12.3	
45.0	7.9	8.4	8.7		
50.0	5.7	6.0			
θ(°)	11~83	20~83	30~83	45~83	60~83
標準フック	65 ton				
フック重量	1000 kg				
巻掛本数	4本				

(単位: ton)

■40.9mブーム+4.35m+21mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
16.0(m)	16.0				
18.0	16.0	16.0			
20.0	16.0	16.0			
22.0	16.0	16.0	16.0		
24.0	16.0	16.0	16.0		
26.0	16.0	16.0	16.0	16.0	
28.0	16.0	16.0	16.0	16.0	14.7
30.0	15.0	15.8	16.0	16.0	14.6
32.0	13.7	14.5	15.2	16.0	14.6
34.0	12.6	13.3	13.9	14.8	14.6
36.0	11.6	12.2	12.8	13.5	14.1
38.0	10.6	11.2	11.7	12.4	12.8
40.0	9.8	10.3	10.8	11.3	
45.0	7.7	8.1	8.5	8.9	
50.0	5.4	5.9	6.2		
55.0	3.5	3.8	4.0		
60.0		1.9			
θ(°)	21~83	22~83	30~83	45~83	60~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■50mブーム+4.35m+21mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
16.0(m)	9.5				
18.0	9.5				
20.0	9.5	9.5			
22.0	9.5	9.5			
24.0	9.5	9.5	9.5		
26.0	9.5	9.5	9.5	9.1	
28.0	9.5	9.5	9.5	9.0	
30.0	9.5	9.5	9.5	8.9	7.4
32.0	9.5	9.5	9.5	8.8	7.4
34.0	9.2	9.5	9.5	8.8	7.4
36.0	8.4	9.0	9.5	8.8	7.4
38.0	7.6	8.2	8.7	8.8	7.4
40.0	6.9	7.4	7.9	8.5	7.4
45.0	5.2	5.6	6.0	6.5	
50.0	3.8	4.2	4.5	4.9	
55.0	2.7	3.0	3.2	3.4	
60.0			2.0		
θ(°)	38~83	38~83	38~83	45~83	60~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■13.6mブーム+4.35m+30mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
14.0(m)	33.0				
16.0	32.4				
18.0	31.8	29.5			
20.0	30.9	27.1			
22.0	28.2	25.1	22.2		
24.0	26.0	23.3	20.8		
26.0	24.1	21.8	19.6		
28.0	22.4	20.5	18.5	15.0	
30.0	21.0	19.3	17.6	14.3	11.2
32.0	19.7	18.3	16.8	13.8	10.9
34.0	18.6	17.4	16.0	13.3	10.6
36.0	17.6	16.6	15.4	13.0	10.5
38.0	16.4	15.9	14.8	12.7	
40.0	15.1	15.2	14.4	12.5	
45.0	12.4				
θ(°)	10~83	20~83	30~83	45~83	60~83
標準フック	65 ton				
フック重量	1000 kg				