

■ショートジブ定格総荷重表

■ショートブーム

単位：t

ブーム長さ(m) 作業半径(m)	9.15	12.20	15.25	18.30	21.35	24.40	27.45	30.50	33.50	36.55	39.60	42.65	45.70	48.75
3.9	6.50													
4.0	6.50													
4.5	6.50	6.50												
5.0	6.50	6.50	6.50	6.50/5.5										
6.0	6.50	6.50	6.50	6.50	6.50	6.50/6.5								
7.0	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50/7.6						
8.0	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50/8.1	6.50/8.6				
9.0	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50/9.2	6.50/9.7		
10.0		6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50/10.2	6.50/10.8
12.0		6.50/11.7	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50
14.0			6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50
16.0				6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50
18.0				6.50/17.0	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.30
20.0					6.50/19.6	6.30	6.10	6.00	5.90	5.80	5.70	5.50	5.40	5.30
22.0						5.40	5.30	5.10	5.10	4.90	4.80	4.70	4.60	4.50
24.0							4.60	4.50	4.40	4.20	4.20	4.00	3.90	3.80
26.0							4.20/24.9	3.90	3.80	3.70	3.60	3.40	3.30	3.20
28.0								3.50/27.5	3.30	3.20	3.10	3.00	2.90	2.70
30.0									2.90	2.80	2.70	2.50	2.40	2.30
32.0										2.40	2.30	2.20	2.10	1.90
34.0										2.30/32.8	2.00	1.90	1.80	1.60
36.0											1.80/35.4	1.60	1.50	1.30
38.0												1.30	1.20	1.10
ロープ掛本数														

■タワーブーム

単位：t

ブーム長さ(m) 作業半径(m)	12.20	15.25	18.30	21.35	24.40	27.45	30.50	33.50	36.55	39.60	42.65	45.70	48.75	51.80
4.5	6.50													
5.0	6.50	6.50	6.50/5.5											
6.0	6.50	6.50	6.50	6.50	6.50/6.5									
7.0	6.50	6.50	6.50	6.50	6.50	6.50	6.50/7.6							
8.0	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50/8.1	6.50/8.6					
9.0	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50/9.2	6.50/9.7			
10.0	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50/10.2	6.50/10.8	6.50/11.3
12.0	6.50/11.7	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50
14.0		6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50
16.0			6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50
18.0			6.50/17.0	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.50	6.40
20.0				6.50/19.6	6.30	6.10	6.00	5.90	5.80	5.70	5.60	5.50	5.40	5.30
22.0					5.40	5.30	5.20	5.10	5.00	4.90	4.80	4.70	4.60	4.50
24.0						4.60	4.50	4.40	4.30	4.20	4.10	4.00	3.90	3.80
26.0						4.20/24.9	4.00	3.90	3.80	3.70	3.50	3.40	3.30	3.20
28.0							3.50/27.5	3.40	3.30	3.20	3.00	2.90	2.80	2.70
30.0								3.00	2.90	2.80	2.60	2.50	2.40	2.30
32.0									2.60	2.50	2.30	2.20	2.00	1.90
34.0									2.50/32.8	2.20	2.00	1.90	1.70	1.50
36.0										2.00/35.5	1.70	1.60	1.40	1.20
38.0											1.40	1.30	1.10	0.90
ロープ掛本数														

1. 上記定格総荷重は、水平堅土上における値で転倒荷重の78%以内、及び移動式クレーン構造規格で定める前方安定度が1.15以上の両方を満足する値です。
2. ショートジブを取付けたままで主フックを使用する時の主フック吊上荷重は、主フックの定格総荷重から0.70tを差し引いた値です。
3. 作業に吊り上げる得る荷重は、上記荷重よりフック、バケット等吊り具一切の重量を差し引いた値です。
4. ショートジブは、クレーン作業以外には使用しないで下さい。