

■ 定格総荷重表

▶ タワー長さ 25.9m

(単位:t)

作業半径 (m)	25.9									
	19.8			22.9						
	90°	75°	60°	90°	75°	60°	90°	75°	60°	
	15.0/8.2m									
9.0	15.0			15.0/9.0m						
10.0	15.0			15.0						
12.0	15.0			15.0						
14.0	15.0			15.0						
16.0	12.9			12.9						
18.0	11.0	9.7/19.6m		11.0						
20.0	9.7	9.5		9.7	8.9/21.1m					
22.0	8.5/22.0m	8.6		8.5	8.4					
24.0		7.7		7.6	7.6					
26.0		6.9		7.1/24.9m	6.8					
28.0		6.3	4.8/29.7m		6.2					
30.0		6.1/28.7m	4.8		5.7	4.3/31.9m				
32.0			4.4		5.3/31.6m	4.3				
34.0			4.1			4.0				
36.0			3.9/34.8m			3.7				
38.0						3.4/37.7m				

表中の太線で囲まれた部分は、ブーム等の強度によって定められた値です。

▶ タワー長さ 29.0m

(単位:t)

作業半径 (m)	29.0										
	19.8			22.9			25.9				
	90°	75°	60°	90°	75°	60°	90°	75°	60°		
	15.0/8.2m										
9.0	15.0			15.0/9.0m					15.0/9.8m		
10.0	15.0			15.0					15.0		
12.0	15.0			15.0					15.0		
14.0	15.0			15.0					15.0		
16.0	12.9			12.9					12.9		
18.0	11.0			11.0					11.0		
20.0	9.7	9.0/20.4m		9.7	8.1/21.9m				9.7		
22.0	8.5/22.0m	8.3		8.5	8.1				8.5	7.4/23.4m	
24.0		7.5		7.6	7.3				7.6	7.2	
26.0		6.7		7.1/24.9m	6.6				6.9	6.5	
28.0		6.1			6.0				6.1/27.8m	5.9	
30.0		5.6/29.4m	4.3/31.3m		5.5					5.4	
32.0			4.1		5.1	3.7/33.4m				5.0	
34.0			3.8		4.9/32.4m	3.6				4.6	3.3/35.6m
36.0			3.5			3.4			4.3/35.3m	3.3	
38.0				3.4/36.3m					3.1		3.0
40.0									2.8/39.2m		2.8
42.0											2.6
44.0											2.5/42.2m

表中の太線で囲まれた部分は、ブーム等の強度によって定められた値です。

▶ タワー長さ 32.0m

(単位:t)

作業半径 (m)	32.0											
	19.8			22.9			25.9			29.0		
	90°	75°	60°	90°	75°	60°	90°	75°	60°	90°	75°	60°
	15.0/8.2m											
9.0	15.0			15.0/9.0m			15.0/9.8m					
10.0	15.0			15.0			15.0			15.0/10.6m		
12.0	15.0			15.0			15.0			15.0		
14.0	15.0			15.0			15.0			15.0		
16.0	12.9			12.9			12.9			12.9		
18.0	11.0			11.0			11.0			11.0		
20.0	9.7	8.4/21.2m		9.7			9.7			9.7		
22.0	8.5/22.0m	8.0		8.5	7.6/22.7m		8.5			8.5		
24.0		7.2		7.6	7.1		7.6	6.8/24.2m		7.6	6.3/25.7m	
26.0		6.5		7.1/24.9m	6.4		6.9	6.3		6.9	6.2	
28.0		5.9			5.8		6.1/27.8m	5.7		6.2	5.7	
30.0		5.4			5.3			5.2		5.6	5.2	
32.0		5.3/30.2m	3.6/32.8m		4.9			4.8		5.2/30.8m	4.8	
34.0			3.4		4.6/33.2m	3.1/35.0m		4.4			4.4	
36.0			3.2			3.0		4.1	2.8/37.1m		4.1	
38.0			2.9/37.8m			2.8		4.1/36.1m	2.7		3.8	2.4/39.3m
40.0						2.6			2.4		3.6/39.1m	2.3
42.0						2.5/40.7m			2.2			2.1
44.0									2.0/43.7m			2.0
46.0												1.8
48.0												1.7/46.6m

表中の太線で囲まれた部分は、ブーム等の強度によって定められた値です。