

■ 定格総荷重表

■ 39.35 m タワー



単位: t

タワー長さ (m)	39.35												タワー長さ (m)
ジブ長さ (m)	24				27				30				ジブ長さ (m)
タワー角 (°) 作業半径 (m)	90	80	70	60	90	80	70	60	90	80	70	60	タワー角 (°) 作業半径 (m)
8.0	20.0 / 8.9												8.0
9.0	20.0 / 8.8				20.0 / 9.5								9.0
10.0	20.0				20.0				20.0 / 10.2				10.0
12.0	20.0				20.0				20.0				12.0
14.0	20.0				20.0				20.0				14.0
15.0	20.0				20.0				20.0				15.0
16.0	19.0				19.0				19.0				16.0
18.0	16.9	16.5 / 19.0			16.9				16.9				18.0
20.0	15.3	16.3			15.3	16.0 / 20.1			15.3	15.0 / 21.2			20.0
22.0	13.9	14.8			13.9	14.8			13.9	14.7			22.0
24.0	11.0	13.6			12.7	13.6			12.8	13.6			24.0
26.0	6.4	12.6			11.0	12.6			11.6	12.6			26.0
28.0		11.7	10.6 / 29.1		7.5	11.7			10.3	11.7			28.0
30.0		11.0	10.3		4.2 / 29.9	11.0	10.0 / 30.7		7.7	11.0			30.0
32.0		10.3	9.6			10.3	9.5		5.0	10.3	9.3 / 32.3		32.0
34.0		10.0 / 32.5	9.0			9.6	8.9		4.0 / 32.8	9.5	8.7		34.0
36.0			8.4			8.8	8.3			8.9	8.1		36.0
38.0			7.8	6.5 / 38.4		8.6 / 36.4	7.7			8.2	7.6		38.0
40.0			7.6 / 39.0	6.1			7.3	5.8 / 40.4		7.3 / 39.3	7.1		40.0
42.0				5.7			6.6	5.6			6.7	5.3 / 42.4	42.0
44.0				5.4			6.4 / 42.9	5.3			6.3	5.1	44.0
46.0				5.3 / 45.1				5.0			5.9 / 45.8	4.8	46.0
48.0								4.6				4.6	48.0
50.0								4.5 / 49.0				4.3	50.0
52.0												4.0 / 51.9	52.0

単位: t

タワー長さ (m)	39.35				タワー長さ (m)
ジブ長さ (m)	33				ジブ長さ (m)
タワー角 (°) 作業半径 (m)	90	80	70	60	タワー角 (°) 作業半径 (m)
10.0	20.0 / 10.8				10.0
12.0	20.0				12.0
14.0	19.9				14.0
15.0	19.4				15.0
16.0	18.9				16.0
18.0	16.9				18.0
20.0	15.3				20.0
22.0	13.9	14.0 / 22.4			22.0
24.0	12.8	13.6			24.0
26.0	11.8	12.6			26.0
28.0	10.5	11.7			28.0
30.0	9.4	11.0			30.0
32.0	8.0	10.2	8.7 / 33.9		32.0
34.0	5.3	9.5	8.6		34.0
36.0	3.0 / 35.7	8.8	8.0		36.0
38.0		8.2	7.5		38.0
40.0		7.7	7.0		40.0
42.0		6.7	6.6		42.0
44.0		6.6 / 42.2	6.2	4.9 / 44.4	44.0
46.0			5.9	4.7	46.0
48.0			5.4	4.5	48.0
50.0			5.3 / 48.7	4.2	50.0
52.0				4.0	52.0
54.0				3.7	53.0
56.0				3.6 / 54.8	54.0