

## ■ 定格総荷重表

## ■ 45.35 m タワー



タワー長さ (m)	45.35												タワー長さ (m)
	24				27				30				
ジブ長さ(m)													ジブ長さ(m)
タワー角 (°)													タワー角 (°)
作業半径 (m)	90	80	70	60	90	80	70	60	90	80	70	60	作業半径 (m)
8.0	20.0/8.9												8.0
9.0	20.0/8.8				20.0/9.6								9.0
10.0	20.0				20.0				20.0/10.2				10.0
12.0	20.0				20.0				20.0				12.0
14.0	20.0				20.0				20.0				14.0
15.0	20.0				20.0				20.0				15.0
16.0	19.0				19.0				19.0				16.0
18.0	16.9				16.9				16.9				18.0
20.0	15.3	15.9			15.3	15.0/21.2			15.3				20.0
22.0	13.9	14.8			13.9	14.8			13.9	14.5/22.3			22.0
24.0	10.8	13.6			12.8	13.6			12.8	13.6			24.0
26.0	6.5	12.6			10.9	12.6			11.6	12.6			26.0
28.0	6.3/26.1	11.7			7.4	11.7			9.9	11.7			28.0
30.0		11.0	9.2/31.2		3.6	11.0			7.8	10.8			30.0
32.0		10.2	9.0			10.1	8.8/32.8		5.6	10.0			32.0
34.0		10.1/33.5	8.3			9.4	8.1		4.8/32.8	9.3	8.1/34.4		34.0
36.0			7.8			8.6	7.7			8.7	7.4		36.0
38.0			7.3			8.1/37.4	7.2			8.1	7.1		38.0
40.0			6.8	5.2/41.4			6.7			7.4	6.6		40.0
42.0			6.5/41.1	5.2			6.3	4.6/43.4		6.9/40.3	6.2		42.0
44.0				4.9			5.8	4.6			5.8	4.2/45.4	44.0
46.0				4.6			5.6/45.0	4.4			5.5	4.2	46.0
48.0				4.2				4.2			4.9/47.9	4.0	48.0
50.0				4.2/48.1				4.0				3.8	50.0
52.0								3.8				3.6	52.0
54.0												3.3	54.0
56.0												3.2/54.9	56.0

タワー長さ (m)	45.35												タワー長さ (m)
	33				36				39				
ジブ長さ(m)													ジブ長さ(m)
タワー角 (°)													タワー角 (°)
作業半径 (m)	90	80	70	60	90	80	70	60	90	80	70	60	作業半径 (m)
10.0	20.0/10.9				16.9/11.5								10.0
12.0	20.0				16.8				13.9/12.2				12.0
14.0	19.8				16.5				13.9				14.0
15.0	19.3				16.3				13.6				15.0
16.0	18.8				16.0				13.4				16.0
18.0	16.9				15.5				13.0				18.0
20.0	15.3				15.1				12.6				20.0
22.0	13.9	13.7/23.4			13.9				12.2				22.0
24.0	12.8	13.6			12.8	13.1/24.5			11.9	11.9/25.7			24.0
26.0	11.8	12.6			11.8	12.4			11.1	11.7			26.0
28.0	10.6	11.7			11.0	11.6			10.4	11.0			28.0
30.0	9.1	10.8			9.7	10.7			9.8	10.5			30.0
32.0	8.1	9.9			8.4	9.8			8.8	9.7			32.0
34.0	5.5	9.2	7.6/35.9		7.7	9.1			7.7	9.1			34.0
36.0	3.1/35.7	8.6	7.5		5.9	8.6	7.0/37.5		7.0	8.6			36.0
38.0		8.1	6.8		4.1	8.1	6.8		6.0	8.1	6.4/39.1		38.0
40.0		7.8	6.5		3.6/38.6	7.8	6.3		4.2	7.7	6.1		40.0
42.0		7.0	6.1			7.4	6.0		3.0/41.5	7.2	5.7		42.0
44.0		6.3/43.2	5.8			6.9	5.7			6.8	5.5		44.0
46.0			5.4	3.9/47.4		6.0	5.4			6.4	5.2		46.0
48.0			5.1	3.9		5.8/46.1	5.1	3.6/49.4		5.7	4.9		48.0
50.0			4.6	3.7			4.8	3.6		5.1/49.0	4.7	3.2/51.4	50.0
52.0			4.4/50.8	3.5			4.5	3.4			4.4	3.2	52.0
54.0				3.3			4.1/53.6	3.2			4.2	3.0	54.0
56.0				3.1				3.0			3.5	2.8	56.0
58.0				3.0/57.8				2.9			3.4/56.5	2.7	58.0
60.0								2.6				2.5	60.0
62.0								2.5/60.7				2.4	62.0
64.0												2.2/63.6	64.0