

■定格総荷重表(6.7m~28.0mブーム)

アウトリガ最大張出(5.8m)(全周)					
作業半径 (m)	6.7m ブーム	11.0m ブーム	15.2m ブーム	21.6m ブーム	28.0m ブーム
3.0	22.00	12.00	12.00	8.00	
3.5	20.00	12.00	12.00	8.00	
4.0	17.00	12.00	12.00	8.00	6.00
4.5	15.00	12.00	12.00	8.00	6.00
5.0		12.00	12.00	8.00	6.00
5.5		12.00	12.00	8.00	6.00
6.0		12.00	11.50	8.00	6.00
6.5		11.30	10.60	8.00	6.00
7.0		9.70	9.40	7.85	6.00
8.0		7.35	7.20	7.10	5.90
9.0		5.70	5.60	6.35	5.35
10.0			4.50	5.25	4.80
11.0			3.60	4.35	4.30
12.0			2.90	3.65	3.85
13.0			2.30	3.05	3.40
14.0				2.60	2.90
15.0				2.20	2.50
16.0				1.80	2.10
17.0				1.50	1.80
18.0				1.20	1.55
19.0				1.00	1.30
20.0				0.85(19.6m)	1.10
21.0					0.95
22.0					0.80
23.0					0.65
24.0					0.50
25.0					0.35
危険角度	-	-	-	-	-

(単位: ton)

アウトリガ中間張出(3.4m)(側方)					
作業半径 (m)	6.7m ブーム	11.0m ブーム	15.2m ブーム	21.6m ブーム	28.0m ブーム
3.0	22.00	12.00	12.00	8.00	
3.5	15.20	12.00	12.00	8.00	
4.0	11.40	11.00	10.00	8.00	6.00
4.5	8.95	8.60	8.40	8.00	6.00
5.0		6.95	6.85	7.00	6.00
5.5		5.75	5.65	6.20	6.00
6.0		4.80	4.70	5.40	5.30
6.5		4.05	3.95	4.65	4.70
7.0		3.45	3.35	4.00	4.15
8.0		2.50	2.40	3.05	3.30
9.0		1.80	1.70	2.35	2.65
10.0			1.10	1.85	2.10
11.0			0.60	1.40	1.65
12.0				1.00	1.30
13.0				0.65	0.95
14.0				0.50(13.5m)	0.70
15.0					0.45
危険角度	-	-	30°	42°	53°

(単位: ton)

アウトリガ中間張出(4.6m)(側方)					
作業半径 (m)	6.7m ブーム	11.0m ブーム	15.2m ブーム	21.6m ブーム	28.0m ブーム
3.0	22.00	12.00	12.00	8.00	
3.5	20.00	12.00	12.00	8.00	
4.0	17.00	12.00	12.00	8.00	6.00
4.5	15.00	12.00	12.00	8.00	6.00
5.0		12.00	12.00	8.00	6.00
5.5		10.00	10.00	8.00	6.00
6.0		8.50	8.40	8.00	6.00
6.5		7.20	7.10	7.90	6.00
7.0		6.20	6.10	6.85	6.00
8.0		4.65	4.55	5.30	5.65
9.0		3.60	3.50	4.20	4.50
10.0			2.70	3.40	3.70
11.0			2.05	2.75	3.05
12.0			1.50	2.25	2.55
13.0			1.05	1.85	2.10
14.0				1.45	1.75
15.0				1.10	1.45
16.0				0.85	1.15
17.0				0.60	0.90
18.0				0.40	0.70
19.0					0.50
20.0					0.35
危険角度	-	-	-	18°	38°

(単位: ton)

アウトリガ最縮小張出(2.04m)(側方)					
作業半径 (m)	6.7m ブーム	11.0m ブーム	15.2m ブーム	21.6m ブーム	28.0m ブーム
3.0	7.80	7.50	7.00	7.00	
3.5	6.10	5.80	5.40	5.60	
4.0	4.80	4.50	4.30	4.55	3.80
4.5	3.80	3.50	3.40	3.80	3.80
5.0		2.80	2.70	3.20	3.25
5.5		2.20	2.10	2.65	2.75
6.0		1.70	1.60	2.25	2.35
6.5		1.30	1.20	1.85	2.00
7.0		0.90	0.80	1.55	1.70
8.0				1.00	1.20
危険角度	-	30°	55°	62°	69°

(単位: ton)