









■ 定格総荷重表

28.0mブーム+5.4mジブ

 (6.0m)							 (5.2m)							 (4.4m)							 (3.4m)											
アウトリガ最大張出(全周)							アウトリガ中間張出(側方)							アウトリガ中間張出(側方)							アウトリガ中間張出(側方)											
ブーム	オフセット 5'	オフセット 25'	オフセット 45'	ブーム	オフセット 5'	オフセット 25'	オフセット 45'	ブーム	オフセット 5'	オフセット 25'	オフセット 45'	ブーム	オフセット 5'	オフセット 25'	オフセット 45'																	
角度	作業半径	荷重	作業半径	荷重	作業半径	荷重	作業半径	角度	作業半径	荷重	作業半径	荷重	作業半径	荷重	作業半径	荷重																
(°)	(m)	(ton)	(m)	(ton)	(m)	(ton)	(m)	(ton)	(m)	(ton)	(m)	(ton)	(m)	(ton)	(m)	(ton)																
81	5.2	3.00	7.0	2.50	8.3	1.55		81	5.2	3.00	7.0	2.50	8.3	1.55			81	5.2	3.00	7.0	2.50	8.3	1.55		81	5.2	3.00	7.0	2.50	8.3	1.55	
77.7	7.2	3.00	8.9	2.50	10.0	1.49		77.7	7.2	3.00	8.9	2.50	10.0	1.49			77.7	7.2	3.00	8.9	2.50	10.0	1.49		77.7	7.2	3.00	8.9	2.50	10.0	1.49	
75	8.9	3.00	10.4	2.30	11.4	1.44		75	8.9	3.00	10.4	2.30	11.4	1.44			75	8.9	3.00	10.4	2.30	11.4	1.44		75	8.9	3.00	10.4	2.30	11.4	1.44	
73	10.0	3.00	11.5	2.14	12.4	1.41		73	10.0	3.00	11.5	2.14	12.4	1.41			73	10.0	3.00	11.5	2.14	12.4	1.41		73	10.0	3.00	11.5	2.14	12.4	1.41	
70	11.7	2.60	13.1	1.94	13.9	1.38		70	11.7	2.60	13.1	1.94	13.9	1.38			70	11.7	2.60	13.1	1.94	13.9	1.38		70	11.7	2.60	13.1	1.94	13.9	1.38	
65	14.3	2.15	15.7	1.69	16.3	1.34		65	14.3	2.15	15.7	1.69	16.3	1.34			65	14.3	2.15	15.7	1.69	16.3	1.34		65	14.3	2.15	15.7	1.69	16.3	1.34	
60	16.8	1.83	18.1	1.49	18.7	1.30		59	17.3	1.77	18.5	1.46	19.1	1.28		64	14.7	1.91	16.1	1.65	16.8	1.33		68	12.6	1.66	14.0	1.45	14.8	1.36		
55	19.2	1.55	20.3	1.35	20.8	1.25		57	18.2	1.53	19.4	1.40	19.9	1.27		62	15.7	1.60	17.1	1.40	17.7	1.31		65	14.1	1.20	15.4	1.07	16.2	1.00		
50	21.3	1.34	22.3	1.19	22.7	1.14		55	19.1	1.31	20.2	1.21	20.8	1.16		60	16.7	1.31	18.0	1.18	18.7	1.11		60	16.5	0.60	17.7	0.53	18.4	0.51		
48	22.1	1.19	23.1	1.11	23.4	1.09		50	21.2	0.88	22.2	0.82	22.6	0.81		55	19.0	0.79	20.0	0.75	20.8	0.67		危険角度	58°		58°		58°			
45	23.3	0.96	24.2	0.91				45	23.2	0.55	24.0	0.53				50	21.1	0.42	22.0	0.41	22.6	0.37										
40	25.1	0.68	25.8	0.65				40	25.0	0.31	25.7	0.29				危険角度	48°		48°		48°											
35	26.7	0.46	27.3	0.44				危険角度	38°		38°		48°																			
30	28.1	0.30	28.5	0.29																												
危険角度	28°		28°		46°																											

28.0mブーム+8.2mジブ

 (6.0m)							 (5.2m)							 (4.4m)							 (3.4m)										
アウトリガ最大張出(全周)							アウトリガ中間張出(側方)							アウトリガ中間張出(側方)							アウトリガ中間張出(側方)										
ブーム	オフセット 5'	オフセット 25'	オフセット 45'	ブーム	オフセット 5'	オフセット 25'	オフセット 45'	ブーム	オフセット 5'	オフセット 25'	オフセット 45'	ブーム	オフセット 5'	オフセット 25'	オフセット 45'																
角度	作業半径	荷重	作業半径	荷重	作業半径	荷重	作業半径	角度	作業半径	荷重	作業半径	荷重	作業半径	荷重	作業半径	荷重															
(°)	(m)	(ton)	(m)	(ton)	(m)	(ton)	(m)	(ton)	(m)	(ton)	(m)	(ton)	(m)	(ton)	(m)	(ton)															
81	6.0	2.00	8.7	1.20	10.2	0.80		81	6.0	2.00	8.7	1.20	10.2	0.80		81	6.0	2.00	8.7	1.20	10.2	0.80		81	6.0	2.00	8.7	1.20	10.2	0.80	
76	9.4	2.00	11.6	1.20	13.0	0.80		76	9.4	2.00	11.6	1.20	13.0	0.80		76	9.4	2.00	11.6	1.20	13.0	0.80		76	9.4	2.00	11.6	1.20	13.0	0.80	
75	10.0	2.00	12.2	1.20	13.6	0.78		75	10.0	2.00	12.2	1.20	13.6	0.78		75	10.0	2.00	12.2	1.20	13.6	0.78		75	10.0	2.00	12.2	1.20	13.6	0.78	
72	11.9	1.81	14.0	1.20	15.2	0.75		72	11.9	1.81	14.0	1.20	15.2	0.75		72	11.9	1.81	14.0	1.20	15.2	0.75		72	11.9	1.81	14.0	1.20	15.2	0.75	
70	13.0	1.71	15.1	1.18	16.3	0.74		70	13.0	1.71	15.1	1.18	16.3	0.74		70	13.0	1.71	15.1	1.18	16.3	0.74		70	13.0	1.71	15.1	1.18	16.3	0.74	
65	15.9	1.49	17.8	1.12	18.8	0.72		65	15.9	1.49	17.8	1.12	18.8	0.72		65	15.9	1.49	17.8	1.12	18.8	0.72		68	13.9	1.46	16.2	1.15	17.3	0.73	
60	18.6	1.33	20.3	1.05	21.1	0.69		60	18.6	1.33	20.3	1.05	21.1	0.69		63	16.9	1.42	18.8	1.09	19.7	0.71		65	15.6	1.03	17.7	0.86	18.8	0.72	
55	21.2	1.20	22.7	0.98	23.2	0.67		56	20.7	1.20	22.2	0.99	22.8	0.68		60	18.5	1.12	20.3	1.00	21.1	0.69		60	18.2	0.50	20.1	0.42	21.1	0.41	
50	23.6	1.04	24.9	0.90	25.2	0.66		55	21.2	1.11	22.7	0.98	23.2	0.67		57	19.9	0.84	21.7	0.74	22.4	0.68		危険角度	58°		58°		58°		
48	24.5	0.99	25.7	0.87	26.0	0.65		50	23.4	0.74	24.9	0.68	25.2	0.65		55	20.9	0.67	22.6	0.60	23.2	0.61									
47	24.8	0.94	26.2	0.85	26.3	0.64		45	25.5	0.45	26.7	0.43				50	23.2	0.34	24.7	0.31											
45	25.6	0.83	26.9	0.78				40	27.4	0.24	28.4	0.24				危険角度	48°		48°		53°										
40	27.5	0.58	28.6	0.55				危険角度	38°		38°		48°																		
35	29.2	0.39	30.0	0.39																											
30	30.7	0.24	31.3	0.24																											
危険角度	28°		28°		45°																										